



Approvals & Certifications

- UL 142, ULC S601, ULC 653
- AS 1940, AS 1692
- TSSA B139ON-2006
- PPG 2 and PPG 26 compliant
- BS 799

Design Features

- Certified and approved bunded Fuel Tanks, compliant with Pollution Prevention Guidelines (PPG2)
- Bidirectional forklift pockets, internal baffles and galvanized lifting eyes to allow easy and safe handling.
- Designed to stack inside shipping containers and across truck beds providing economical transportation.
- Unique hex corners for extra strength and Hose Openings in front of allow tank to be used when locked.
- Provisions for pumps and bund alarm as well as feed and return
- Connections for generator use with provisions for additional feed and returns for multiple generator use.
- Bunded outer tank capacity 110% of volume and removable inner tank for maintenance or cleaning.
- Two lifting plates on primary/inner tank, one at each end, which are removable for maintenance/access. Secure lid with lockable access hatch.
- Space efficient design: Easily stacked 2 high when full and 3 high when empty. Lifting when empty only.

SPECIFICATIONS			
Primary Fitting Plate	2" Fill Point: 1 ½" Level Gauge: 2" Pressure Vacuum Vent: 2" Breather Vent		
	1 x 1 ½" Feed Socket: 1 x 1 ½" Return Sockets: (with provisions for an additional 1 ½" Feed & 1 ½" Return)		
Secondary Fitting Plate	Supplied with blank plates as standard. Can be supplied with optional 2" Socket: 1" Socket		
Capacity (Litres)	10000	Bund Tank Material Thickness (mm)	3
Capacity (US Gallons)	2642	Inner Tank Material Thickness (mm)	6
Length (mm)	5800	Weight, Tare (kg)	4090
Width (mm)	2220	Weight, Laden (kg)	13090
Height (mm)	1075	Safe fuel fill levels (Litres)	9500
*Calculations based on safe fuel fill levels as 95% of total tank capacity & specific gravity of diesel as 0.9			



BUNDED TANK

Generic Illustration



REMOVABLE INNER TANK

FH-10000L

