



Approvals & Certifications

- UL 142, ULC S601, ULC 653
- Transport Canada CGSB 43.146-2002
- TSSA B139ON-2006
- AS 1940, AS 1692
- PPG 2 & PPG 26 compliant
- Vibration Tested
- BS 799



Design Features

- Certified and approved bunded Fuel Tanks, compliant with Pollution Prevention Guidelines.
- Lifting when full certified.
- Bidirectional forklift pockets, internal baffles & galvanized lifting eyes to allow easy and safe handling.
- Designed to stack inside shipping containers & across truck beds providing economical transportation.
- Unique hex corners for extra strength and hose openings in front of allow tank to be used when locked.
- Provisions for pumps & bund alarm as well as feed and returns.
- Connections with provisions for additional feed returns for multiple equipment use.
- Bunded outer tank capacity 110% of volume & removable inner tank for maintenance.
- Two lifting plates on primary/inner tank, one at each end, which are removable for maintenance/access.
- Secure lid with lockable access hatch.
- Space efficient design: easily stacked 2 high when full & 3 high when empty.

SPECIFICATIONS			
Primary Fitting Plate	2" Fill Point: 1 ½" Level Gauge: 2" Pressure Vacuum Vent: 2" Breather Vent		
	1 x 1 ½" Feed Socket: 1 x 1 ½" Return Sockets: (with provisions for an additional 1 ½" Feed & 1 ½" Return)		
Secondary Fitting Plate	Supplied with blank plates as standard. Can be supplied with optional 1 ½" Socket		
Capacity (Litres)	3000	Bund Tank Material Thickness (mm)	3
Capacity (US Gallons)	793	Inner Tank Material Thickness (mm)	3
Length (mm)	2525	Weight, Tare (kg)	1180
Width (mm)	1600	Weight, Laden (kg)	3880
Height (mm)	1075	Safe fuel fill levels (Litres)	2850
*Calculations based on safe fuel fill levels as 95% of total tank capacity & specific gravity of diesel as 0.9			



BUNDED TANK

Generic Illustration



REMOVABLE INNER TANK

FH-3000L

